

PRODUCT FEATURES

- High Short Circuit Capability
- Free wheeling diodes with fast and soft reverse recovery
- $V_{CE(sat)}$ with positive temperature coefficient
- Ultra Low Loss, High Ruggedness
- UL recognized, file no. E332185



APPLICATIONS

- Inverter Convertor
- Welder SMPS and UPS
- Induction Heating

IGBT-inverter

ABSOLUTE MAXIMUM RATINGS

$T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Values	Unit
V_{CES}	Collector Emitter Voltage	$T_J = 25^\circ\text{C}$	1200	V
V_{GES}	Gate Emitter Voltage		± 20	
I_C	DC Collector Current	$T_C = 25^\circ\text{C}$	150	A
		$T_C = 80^\circ\text{C}$	100	
I_{CM}	Repetitive Peak Collector Current	$t_p = 1\text{ms}$	200	
P_{tot}	Power Dissipation Per IGBT		830	W

Diode-inverter

ABSOLUTE MAXIMUM RATINGS

$T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Values	Unit
V_{RRM}	Repetitive Reverse Voltage	$T_J = 25^\circ\text{C}$	1200	V
$I_{F(AV)}$	Average Forward Current	$T_C = 25^\circ\text{C}$	100	A
I_{FRM}	Repetitive Peak Forward Current	$t_p = 1\text{ms}$	200	
i^2t		$T_J = 125^\circ\text{C}, t = 10\text{ms}, V_R = 0\text{V}$	3200	A^2S

IGBT-inverter

ELECTRICAL CHARACTERISTICS

 $T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit	
$V_{GE(th)}$	Gate Emitter Threshold Voltage	$V_{CE}=V_{GE}, I_C=4\text{mA}$	5.0	6.2	7.0	V	
$V_{CE(sat)}$	Collector Emitter Saturation Voltage	$I_C=100\text{A}, V_{GE}=15\text{V}, T_J=25^\circ\text{C}$		1.8	2.4		
		$I_C=100\text{A}, V_{GE}=15\text{V}, T_J=125^\circ\text{C}$		2.0			
I_{CES}	Collector Leakage Current	$V_{CE}=1200\text{V}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$			1	mA	
		$V_{CE}=1200\text{V}, V_{GE}=0\text{V}, T_J=125^\circ\text{C}$			10	mA	
I_{GES}	Gate Leakage Current	$V_{CE}=0\text{V}, V_{GE}=\pm 15\text{V}, T_J=25^\circ\text{C}$	-400		400	nA	
R_{gint}	Integrated Gate Resistor			5		Ω	
Q_g	Gate Charge	$V_{CE}=600\text{V}, I_C=100\text{A}, V_{GE}=\pm 15\text{V}$		1.2		μC	
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, V_{GE}=0\text{V}, f=1\text{MHz}$		8.58		nF	
C_{res}	Reverse Transfer Capacitance				400		pF
$t_{d(on)}$	Turn on Delay Time	$V_{CC}=600\text{V}, I_C=100\text{A}$ $R_G=7.5\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		230		ns
			$T_J=125^\circ\text{C}$		260		ns
t_r	Rise Time	Inductive Load	$T_J=25^\circ\text{C}$		65		ns
			$T_J=125^\circ\text{C}$		70		ns
$t_{d(off)}$	Turn off Delay Time	$V_{CC}=600\text{V}, I_C=100\text{A}$ $R_G=7.5\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		500		ns
			$T_J=125^\circ\text{C}$		570		ns
t_f	Fall Time	Inductive Load	$T_J=25^\circ\text{C}$		70		ns
			$T_J=125^\circ\text{C}$		90		ns
E_{on}	Turn on Energy	$V_{CC}=600\text{V}, I_C=100\text{A}$ $R_G=7.5\Omega,$ $V_{GE}=\pm 15\text{V},$ Inductive Load	$T_J=25^\circ\text{C}$		7.8		mJ
			$T_J=125^\circ\text{C}$		9.9		mJ
E_{off}	Turn off Energy	Inductive Load	$T_J=25^\circ\text{C}$		7.6		mJ
			$T_J=125^\circ\text{C}$		11		mJ
I_{sc}	Short Circuit Current	$tpsc \leq 10\mu\text{s}, V_{GE}=15\text{V}$ $T_J=125^\circ\text{C}, V_{CC}=900\text{V}$		540		A	
R_{thJC}	Junction to Case Thermal Resistance (Per IGBT)				0.15	K/W	

Diode-inverter

ELECTRICAL CHARACTERISTICS

 $T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
V_F	Forward Voltage	$I_F=100\text{A}, V_{GE}=0\text{V}, T_J=25^\circ\text{C}$		1.85	2.4	V
		$I_F=100\text{A}, V_{GE}=0\text{V}, T_J=125^\circ\text{C}$		1.80		
t_{rr}	Reverse Recovery Time	$I_F=100\text{A}, V_R=600\text{V}$		140		ns
I_{RRM}	Max. Reverse Recovery Current	$di_F/dt=-2300\text{A}/\mu\text{s}$		131		A
Q_{RR}	Reverse Recovery Charge	$T_J=125^\circ\text{C}$		14.5		μC
E_{rec}	Reverse Recovery Energy				5.4	
R_{thJCD}	Junction to Case Thermal Resistance (Per Diode)				0.3	K/W

MODULE CHARACTERISTICS

$T_C = 25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Values	Unit
T_{Jmax}	Max. Junction Temperature		150	°C
T_{Jop}	Operating Temperature		-40~125	
T_{stg}	Storage Temperature		-40~125	
V_{isol}	Isolation Breakdown Voltage	AC, 50Hz(R.M.S), t=1minute	3000	V
CTI	Comparative Tracking Index		> 225	
Torque	to heatsink	Recommended (M6)	3~5	Nm
	to terminal	Recommended (M6)	2.5~5	Nm
Weight			300	g




Figure 1. Typical Output Characteristics IGBT-inverter




Figure 2. Typical Output Characteristics IGBT-inverter




Figure 3. Typical Transfer Characteristics IGBT-inverter




Figure 4. Switching Energy vs Gate Resistor IGBT-inverter




Figure 5. Switching Energy vs Collector Current IGBT-inverter




Figure 6. Reverse Biased Safe Operating Area IGBT-inverter




Figure 7. Collector Current vs Case temperature IGBT-inverter




Figure 8. Forward current vs Case temperature Diode-inverter




Figure 9. Diode Forward Characteristics Diode-inverter




Figure 10. Switching Energy vs Gate Resistor Diode-inverter





Figure 11. Switching Energy vs Forward Current Diode-inverter

Figure 12. Transient Thermal Impedance of Diode and IGBT-inverter





Figure 13. Circuit Diagram



Dimensions in (mm)
Figure 14. Package Outline