

## **PRODUCT FEATURES**

- High level of integration
- 600V IGBT<sup>3</sup> CHIP(Trench+Field Stop technology)
- Low saturation voltage and positive temperature coefficient
- Fast switching and short tail current
- Free wheeling diodes with fast and soft reverse recovery
- Industry standard package with insulated copper base plate and soldering pins for PCB mounting
- Temperature sense included

## **APPLICATIONS**

- AC motor control
- Motion/servo control
- Inverter and power supplies



Rectifier+Brake+Inverter

## IGBT-inverter

ABSOLUTE MAXIMUM RATINGS( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
$V_{CES}$	Collector Emitter Voltage	$T_J=25^\circ\text{C}$	600	V
$V_{GES}$	Gate Emitter Voltage		$\pm 20$	
$I_C$	DC Collector Current	$T_C=25^\circ\text{C}, T_{Jmax}=175^\circ\text{C}$	125	A
		$T_C=70^\circ\text{C}, T_{Jmax}=175^\circ\text{C}$	100	
$I_{CM}$	Repetitive Peak Collector Current	$t_p=1\text{ms}$	200	
$P_{tot}$	Power Dissipation Per IGBT	$T_C=25^\circ\text{C}, T_{Jmax}=175^\circ\text{C}$	330	W

## Diode-inverter

ABSOLUTE MAXIMUM RATINGS ( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
$V_{RRM}$	Repetitive Reverse Voltage	$T_J=25^\circ\text{C}$	600	V
$I_{F(AV)}$	Average Forward Current		100	
$I_{FRM}$	Repetitive Peak Forward Current	$t_p=1\text{ms}$	200	A
$I^2t$		$T_J=125^\circ\text{C}, t=10\text{ms}, V_R=0\text{V}$	1000	

MacMic Science & Technology Co., Ltd.

Add: #18, Hua Shan Zhong Lu, New District, Changzhou City, Jiangsu Province, P. R .of China

Tel.: +86-519-85163708 Fax: +86-519-85162291 Post Code: 213022 Website: [www.macmicst.com](http://www.macmicst.com)

# MMG100W060XB6EN

IGBT-inverter

ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit	
$V_{GE(\text{th})}$	Gate Emitter Threshold Voltage	$V_{CE}=V_{GE}$ , $I_C=1.6\text{mA}$	4.9	5.8	6.5	V	
$V_{CE(\text{sat})}$	Collector Emitter Saturation Voltage	$I_C=100\text{A}$ , $V_{GE}=15\text{V}$ , $T_J=25^\circ\text{C}$		1.45	1.9		
		$I_C=100\text{A}$ , $V_{GE}=15\text{V}$ , $T_J=125^\circ\text{C}$		1.6			
$I_{CES}$	Collector Leakage Current	$V_{CE}=600\text{V}$ , $V_{GE}=0\text{V}$ , $T_J=25^\circ\text{C}$			1	mA	
		$V_{CE}=600\text{V}$ , $V_{GE}=0\text{V}$ , $T_J=125^\circ\text{C}$			5	mA	
$I_{GES}$	Gate Leakage Current	$V_{CE}=0\text{V}$ , $V_{GE}=\pm 15\text{V}$ , $T_J=25^\circ\text{C}$	-400		400	nA	
$R_{gint}$	Integrated Gate Resistor			2		$\Omega$	
$Q_g$	Gate Charge	$V_{CE}=300\text{V}$ , $I_C=100\text{A}$ , $V_{GE}=\pm 15\text{V}$		1.1		$\mu\text{C}$	
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}$ , $V_{GE}=0\text{V}$ , $f=1\text{MHz}$		6.2		nF	
$C_{res}$	Reverse Transfer Capacitance			190		pF	
$t_{d(on)}$	Turn on Delay Time	$V_{CC}=300\text{V}$ , $I_C=100\text{A}$ , $R_G=3.3\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	70		ns	
			$T_J=125^\circ\text{C}$	80		ns	
$t_r$	Rise Time		$T_J=25^\circ\text{C}$	20		ns	
			$T_J=125^\circ\text{C}$	20		ns	
$t_{d(off)}$	Turn off Delay Time	$V_{CC}=300\text{V}$ , $I_C=100\text{A}$ , $R_G=3.3\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	260		ns	
			$T_J=125^\circ\text{C}$	290		ns	
$t_f$	Fall Time		$T_J=25^\circ\text{C}$	70		ns	
			$T_J=125^\circ\text{C}$	70		ns	
$E_{on}$	Turn on Energy	$V_{CC}=300\text{V}$ , $I_C=100\text{A}$ , $R_G=3.3\Omega$ , $V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	0.3		mJ	
			$T_J=125^\circ\text{C}$	0.7		mJ	
$E_{off}$	Turn off Energy		$T_J=25^\circ\text{C}$	2.5		mJ	
			$T_J=125^\circ\text{C}$	3.35		mJ	
$I_{SC}$	Short Circuit Current	$tpsc \leq 6\mu\text{s}$ , $V_{GE}=15\text{V}$ , $T_J=125^\circ\text{C}$ , $V_{CC}=360\text{V}$		500		A	
$R_{thJC}$	Junction to Case Thermal Resistance ( Per IGBT )				0.45	K /W	

Diode-inverter

ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_F$	Forward Voltage	$I_F=100\text{A}$ , $V_{GE}=0\text{V}$ , $T_J=25^\circ\text{C}$		1.55	1.95	V
		$I_F=100\text{A}$ , $V_{GE}=0\text{V}$ , $T_J=125^\circ\text{C}$		1.50		
$t_{rr}$	Reverse Recovery Time			130		ns
$I_{RRM}$	Max. Reverse Recovery Current	$I_F=100\text{A}$ , $V_R=300\text{V}$ , $dI_F/dt=-5100\text{A}/\mu\text{s}$		150		A
$Q_{RR}$	Reverse Recovery Charge	$T_J=125^\circ\text{C}$		8		$\mu\text{C}$
$E_{rec}$	Reverse Recovery Energy			2.25		mJ
$R_{thJCD}$	Junction to Case Thermal Resistance ( Per Diode )				0.8	K /W

# MMG100W060XB6EN

## Diode-RECTIFIER

ABSOLUTE MAXIMUM RATINGS ( $T_c=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
$V_{RRM}$	Repetitive Reverse Voltage	$T_J=25^\circ\text{C}$	1600	V
$I_{F(AV)}$	Average Forward Current Per Diode	$T_c=80^\circ\text{C}$	80	
$I_{FRMS}$	R.M.S. Forward Current Per Diode		125	
$I_{RMS}$	R.M.S. Current at rectifier output		150	
$I_{FSM}$	Non Repetitive Surge Forward Current	$T_J=45^\circ\text{C}$ , $t=10\text{ms}$ , 50Hz	1050	A
		$T_J=45^\circ\text{C}$ , $t=8.3\text{ms}$ , 60Hz	1151	
$I^2t$		$T_J=45^\circ\text{C}$ , $t=10\text{ms}$ , 50Hz	5510	$\text{A}^2\text{s}$
		$T_J=45^\circ\text{C}$ , $t=8.3\text{ms}$ , 60Hz	5508	

## Diode-RECTIFIER

ELECTRICAL CHARACTERISTICS ( $T_c=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_F$	Forward Voltage	$I_F=100\text{A}$ , $T_J=25^\circ\text{C}$		1.1	1.3	V
		$I_F=100\text{A}$ , $T_J=150^\circ\text{C}$		1.04		V
$I_R$	Reverse Leakage Current	$V_R=1600\text{V}$ , $T_J=25^\circ\text{C}$			50	$\mu\text{A}$
		$V_R=1600\text{V}$ , $T_J=150^\circ\text{C}$			1	mA
$R_{thJCD}$	Junction to Case Thermal Resistance ( Per Diode )				0.46	K /W

## IGBT-Brake chopper

ABSOLUTE MAXIMUM RATINGS ( $T_c=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
$V_{CES}$	Collector Emitter Voltage	$T_J=25^\circ\text{C}$	600	V
$V_{GES}$	Gate Emitter Voltage		$\pm 20$	
$I_C$	DC Collector Current	$T_c=25^\circ\text{C}$ , $T_{Jmax}=175^\circ\text{C}$	95	A
		$T_c=70^\circ\text{C}$ , $T_{Jmax}=175^\circ\text{C}$	75	
$I_{CM}$	Repetitive Peak Collector Current	$t_p=1\text{ms}$	150	
$P_{tot}$	Power Dissipation Per IGBT	$T_c=25^\circ\text{C}$ , $T_{Jmax}=175^\circ\text{C}$	250	W

## Diode-Brake chopper

ABSOLUTE MAXIMUM RATINGS ( $T_c=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Values	Unit
$V_{RRM}$	Repetitive Reverse Voltage	$T_J=25^\circ\text{C}$	600	V
$I_{F(AV)}$	Average Forward Current	$t_p=1\text{ms}$	50	A
$I_{FRM}$	Repetitive Peak Forward Current		100	
$I^2t$	$T_J=125^\circ\text{C}$ , $t=10\text{ms}$ , $V_R=0\text{V}$		330	$\text{A}^2\text{s}$

# MMG100W060XB6EN

IGBT-Brake chopper

ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_{GE(\text{th})}$	Gate Emitter Threshold Voltage	$V_{CE}=V_{GE}$ , $I_C=1.2\text{mA}$	4.9	5.8	6.5	V
$V_{CE(\text{sat})}$	Collector Emitter Saturation Voltage	$I_C=75\text{A}$ , $V_{GE}=15\text{V}$ , $T_J=25^\circ\text{C}$		1.45	1.9	
		$I_C=75\text{A}$ , $V_{GE}=15\text{V}$ , $T_J=125^\circ\text{C}$		1.6		
$I_{CES}$	Collector Leakage Current	$V_{CE}=600\text{V}$ , $V_{GE}=0\text{V}$ , $T_J=25^\circ\text{C}$			1	mA
		$V_{CE}=600\text{V}$ , $V_{GE}=0\text{V}$ , $T_J=125^\circ\text{C}$			5	mA
$I_{GES}$	Gate Leakage Current	$V_{CE}=0\text{V}$ , $V_{GE}=\pm 15\text{V}$ , $T_J=25^\circ\text{C}$	-400		400	nA
$R_{gint}$	Integrated Gate Resistor			0		$\Omega$
$Q_g$	Gate Charge	$V_{CE}=300\text{V}$ , $I_C=75\text{A}$ , $V_{GE}=\pm 15\text{V}$		0.8		$\mu\text{C}$
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}$ , $V_{GE}=0\text{V}$ , $f=1\text{MHz}$		4.6		nF
$C_{res}$	Reverse Transfer Capacitance			145		pF
$t_{d(on)}$	Turn on Delay Time	$V_{CC}=300\text{V}$ , $I_C=75\text{A}$ $R_G = 5.1\Omega$ ,	$T_J=25^\circ\text{C}$	25		ns
			$T_J=125^\circ\text{C}$	25		ns
$t_r$	Rise Time	$V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	20		ns
			$T_J=125^\circ\text{C}$	20		ns
$t_{d(off)}$	Turn off Delay Time	$V_{CC}=300\text{V}$ , $I_C=75\text{A}$ $R_G = 5.1\Omega$ ,	$T_J=25^\circ\text{C}$	210		ns
			$T_J=125^\circ\text{C}$	240		ns
$t_f$	Fall Time	$V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	60		ns
			$T_J=125^\circ\text{C}$	70		ns
$E_{on}$	Turn on Energy	$V_{CC}=300\text{V}$ , $I_C=75\text{A}$ $R_G = 5.1\Omega$ ,	$T_J=25^\circ\text{C}$	0.35		mJ
			$T_J=125^\circ\text{C}$	0.5		mJ
$E_{off}$	Turn off Energy	$V_{GE}=\pm 15\text{V}$ , Inductive Load	$T_J=25^\circ\text{C}$	2.4		mJ
			$T_J=125^\circ\text{C}$	2.8		mJ
$I_{SC}$	Short Circuit Current	$tpsc \leq 6\mu\text{s}$ , $V_{GE}=15\text{V}$ $T_J=125^\circ\text{C}$ , $V_{CC}=360\text{V}$		380		A
$R_{thJC}$	Junction to Case Thermal Resistance ( Per IGBT )				0.6	K /W

Diode-Brake chopper

ELECTRICAL CHARACTERISTICS ( $T_C=25^\circ\text{C}$  unless otherwise specified)

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$V_F$	Forward Voltage	$I_F=50\text{A}$ , $V_{GE}=0\text{V}$ , $T_J=25^\circ\text{C}$		1.55	1.95	V
		$I_F=50\text{A}$ , $V_{GE}=0\text{V}$ , $T_J=125^\circ\text{C}$		1.50		
$I_{RRM}$	Max. Reverse Recovery Current	$I_F=50\text{A}$ , $V_R=300\text{V}$ $dI_F/dt=-900\text{A}/\mu\text{s}$		34		A
$Q_{RR}$	Reverse Recovery Charge			2.85		$\mu\text{C}$
$E_{rec}$	Reverse Recovery Energy	$T_J=125^\circ\text{C}$		0.5		mJ
$R_{thJCD}$	Junction to Case Thermal Resistance (Per Diode)				1.2	K /W

# MMG100W060XB6EN

**NTC CHARACTERISTICS ( $T_c=25^\circ\text{C}$  unless otherwise specified)**

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
$R_{25}$	Resistance	$T_c = 25^\circ\text{C}$		5		$\text{k}\Omega$
$B_{25/50}$	$R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298.15 \text{ K}))]$			3375		K

**MODULE CHARACTERISTICS ( $T_c=25^\circ\text{C}$  unless otherwise specified)**

Symbol	Parameter/Test Conditions	Values	Unit
$T_{Jmax}$	Max. Junction Temperature	175	$^\circ\text{C}$
		150	
$T_{Jop}$	Operating Temperature	-40~150	
$T_{stg}$	Storage Temperature	-40~125	
$V_{isol}$	Isolation Breakdown Voltage	3000	V
CTI	Comparative Tracking Index	>200	
Md	Mounting Torque	2.5~5	Nm
Weight		300	g




Figure 1. Typical Output Characteristics IGBT-inverter




Figure 2. Typical Output Characteristics IGBT-inverter




Figure 3. Typical Transfer characteristics IGBT-inverter




Figure 4. Switching Energy vs Gate Resistor IGBT-inverter




Figure 5. Switching Energy vs Collector Current IGBT-inverter




Figure 6. Reverse Biased Safe Operating Area IGBT-inverter




Figure 7. Diode Forward Characteristics Diode -inverter




Figure 8. Switching Energy vs Gate Resistor Diode -inverter




Figure 9. Switching Energy vs Forward Current Diode-inverter




Figure 10. Transient Thermal Impedance of Diode and IGBT-inverter




Figure 11. Diode Forward Characteristics Diode- rectifier




Figure 12. Typical Output Characteristics IGBT- brake chopper




Figure 13. Diode Forward Characteristics Diode - brake chopper




Figure 14. NTC Characteristics




Figure 15. Collector Current vs Case temperature  
IGBT -inverter




Figure 16. Forward current vs Case temperature  
Diode -inverter





Figure 17. Circuit Diagram



Dimensions in (mm)

Figure 18. Package Outline